



Grease EP00/000 used in Hydynamic pre-filled Polyamide tubes.

Grease EP 00/000 is made of high-quality basic oils by means of lithium soaps as thickening agents. The product contains additives for improving the rust and oxidation protection, the adhesive strength and the pressure absorption capacity.

Practical advantages:

Grease EP 00/000 is appropriate for all lubrication points which are provided from the central lubricating systems for utility vehicles.

Approvals:

- MB 264.0
- MAN 283 Li-P 00/000
- VOGEL/SKF Lubrication Systems

Typical characteristics:

Properties	Value	Unit	Test method
Appearance	smooth, homogeneous	-	-
Colour	beige-brown	-	-
Thickener	Lithium	-	-
NLGI grade	00/000	-	DIN 51 818
Worked penetration	435-450	1/10 mm	ASTM D 217
Dropping point	165	°C	ASTM 2265
Viscosity, kin. At 40 °C (Baseoil)	40	mm ² /s	ASTM D 7042
EMCOR Corrosion test	0-0	degree of corrosion	DIN 51 802
Flow pressure at -40°C	48	mbar	DIN 51 805
Operating temperature range	-40 to +120	°C	DIN 51 825
DIN-Identification	GP 00/000 K-40	-	DIN 51 502
ISO-Identification	ISO-L-X-DCBB 00/000	-	ISO 6743-9